## AMENDMENTS TO THE CLAIMS

## **CLAIMS**

## WHAT IS CLAIMED IS:

1. (Original) A grip for a golf club, the grip including a wide portion of substantially uniform, substantially rectangular cross-section, said wide portion having a front face, a rear face and two side faces, wherein the wide portion is of sufficient width to allow the club to be gripped by a golfer with both hands at the same height and both thumbs side-by-side on the front face of the wide portion, and the width to depth ratio of the wide portion is in the range 1.3 to 2.0: 1.

- 2. (Currently amended) A grip according to claim 1, in which the front face is convex.
- 3. (Original)) A grip for a golf club, the grip including a wide portion of substantially uniform, substantially rectangular cross-section, said wide portion having a front face, a rear face and two side faces, wherein the wide portion is of sufficient width to allow the club to be gripped by a golfer with both hands at the same height and both thumbs side-by-side on the front face of the wide portion, and wherein the front surface is convex and the rear and side surfaces are substantially planar.
- 4. (Original) A grip according to claim 3 in which the width to depth ratio of the grip is in the range 1.3 to 2.0: 1.
- 5. (Currently amended) A grip according to any one of the preceding claims claim 4, in which the width to depth ratio is in the range 1.4 to 1.8: 1, preferably in the range 1.4 to 1.6: 1, and more preferably approximately 1.5: 1.
- 6. (Currently amended) A grip according to any one of the preceding claims claim 1 or claim 3, wherein the front face is arcuate, having a radius of curvature in the range 50-65mm.

7. (Currently amended) A grip according to any one of the preceding claims claim 1

or claim 3, in which the intersections of the front face and the rear face with each side face are

rounded.

8. (Currently amended) A grip according to any one of the preceding claims claim 1

or claim 3, in which the wide portion of the grip has a width at the widest point thereof in the

range 30-60mm, and preferably in the range 40-50mm.

9. (Currently amended) A grip according to any one of the preceding claims claim 1

or claim 3, in which the wide portion has a length in the range 150-300mm, and preferably in the

range 180-250mm.

10. (Currently amended) A grip according to any one of the preceding claims claim 1

or claim 3, in which the grip has a tapered portion at its lower end.

11. (Currently amended) A grip according to any one of the preceding claims claim 1

or claim 3, wherein the overall length of the grip is in the range 200-400mm, and preferably in

the range 250-300mm.

12. (Currently amended) A grip according to any one of the preceding claims claim 1

or claim 3, in which the grip includes an elongate body member and a separate end cap for

attachment to the upper end of the body member.

13. (Original) A grip according to claim 12, in which the end cap includes locating

formations for engagement with the body member.

14. (Original) A grip according to claim 13, in which the end cap includes lugs for

engagement with elongate bores in the body member.

15. (Original) A grip for a golf club, wherein the gulp includes an elongate body

member and a separate end cap for attachment to the upper end of the body member.

-4-

16. (Original) A grip according to claim 15, in which the body member has a portion of uniform cross-section at its upper end.

- 17. (Currently amended) A grip according to claim 15 or 16, in which the end cap includes locating formations for engagement with the body member.
- 18. (Original) A grip according to claim 17, in which the end cap includes lugs for engagement with elongate bores in the body member.
- 19. (Original) A grip according to claim 18, in which the elongate bores extend along a substantial part of the length of the grip, and preferably at least 20% percent of the length of the grip.
- 20. (Currently amended) A golf club including a grip according to any-one-of-the preceding claims 1, 3 or 15.
  - 21. (Original) A golf club according to claim 20, in which the golf club is a putter.
- 22. (Original) A method of adjusting the length of a golf club grip, wherein the grip includes a body member and a separate end cap attached thereto, said method including detaching the separate end cap from the body member, removing part of the body member, end reattaching the separate end cap to the remainder of the body member.
- 23. (Original) A method according to claim 22, in which the body member includes elongate bores formed in the body member and the separate end cap includes formations for engaging the elongate bores.
- 24. (Currently amended) A method according to claim 22 or 23, wherein the grip is as claimed in any one of claims 1 to 24, 3 or 15.
- 25. (New) A grip according to claim 5, in which the width to depth ratio is in the range 1.4 to 1.6:1.

- 26. (New) A grip according to claim 25, in which the width to depth ratio is about 1.5:1.
- 27. (New) A grip according to claim 8, in which the wide portion of the grip has a width at the widest point thereof in the range 40-50mm.
- 28. (New) A grip according to claim 9, in which the wide portion has a length in the range 180-250mm.
- 29. (New) A grip according to claim 11, wherein the overall length of the grip is in the range 250-300mm.